## TSC TTP-244ME

TTP-244ME		
Introduction		Image
receiving reliable performa 100mm per second (4.0 ips	2-year warranty, giving you the confidence of ince day in and day out. With print speeds up to ) and a large 2MB DRAM memory capacity, the ed and efficiency you need to keep running.	
Specifications		
Printing Method	Thermal transfer and/or direct thermal	
Print Speed	38mm, 50mm, 76mm, 100mm per second (1.5, 2.0, 3.0, 4.0 ips)	
Resolution	203dpi	
Print Width	25mm-104mm	
Print Length	7mm-2286mm	
Memory	512K FLASH ROM & 2M DRAM	
Communication Interfaces	RS232 and Centronics Parallel ports	
Dimension	295mm W x 360mm D x 220mm H (11.6" W x 14.2" D x 8.7" H)	
Bar Code	Code 39, Code 93, Code 128 UCC, Code 128 subsets A.B.C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 & 5 digits add-on PDF-417, Maxicode, DataMatrix	
Fonts	Five alphanumeric fonts 0, 90, 180, 270 degrees	
Software	LabelView XLT+? and Windows Drivers	
Ribbon Length	300M	
Ribbon Width	25.4mm -110mm	
Sensors	Label gap, ribbon end, black-mark	
Options & Accessories	Stand-alone KDU Cutter International Fonts Memory Expansion	